

WEST

L13: Entry 14 of 21

File: JPAB

Feb 20, 1990

PUB-NO: JP402050628A
DOCUMENT-IDENTIFIER: JP 02050628 A
TITLE: RADIO RECEIVER

PUBN-DATE: February 20, 1990

INVENTOR-INFORMATION:

| NAME | COUNTRY |
|--------------------|---------|
| KAWAI, KOZO | |
| TOKITOU, TOSHIAKI | |
| YAMAZAKI, HIDENORI | |

ASSIGNEE-INFORMATION:

| NAME | COUNTRY |
|-------------------------------|---------|
| MATSUSHITA ELECTRIC WORKS LTD | |

APPL-NO: JP63202339
APPL-DATE: August 12, 1988

US-CL-CURRENT: 369/7; 369/FOR.118
INT-CL (IPC): H04B 1/20; H04B 1/16

ABSTRACT:

PURPOSE: To simplify reproduction and to realize immediate reproduction by forming a control means in a way that a head of an audio signal recorded automatically is reproduced in the operation of a reproduction switch in a radio set provided with a recording and reproducing means.

CONSTITUTION: The radio set is provided with a radio main body 1, a recording and reproducing means 2 recording a broadcast audio signal received by the radio main body 1 and reproducing the recorded broadcast voice, a timer means 3 setting the recording time of the broadcast voice and a control means 4 controlling the radio main body 1 and the recording and reproducing means 2 by an output of the timer means 3 to record a routine time program automatically, and the control means 4 is formed so that a signal is regenerated from the head of the broadcast voice recorded automatically in the operation of a reproduction switch 5. The recording and reproducing means 2 uses an endless magnetic tape 20, and the start and the end of the magnetic tape 20 are jointed by a conductive tape and the one cycle stop position at the recording and reproduction is recognized by using a sensing switch 28 to detect the conductive tape.

COPYRIGHT: (C)1990, JPO&Japio

- 1 … ラジオ本体
- 2 … 録音再生手段
- 3 … タイマー手段
- 4 … 制御手段
- 5 … 再生スイッチ

